



## 5MP Full-color HD Analog Turret Camera

### SHD-VD501LCM

#### FEATURES

- 5MP 20fps/4MP real-time image, high resolution, true color
- AHD / TVI / CVI standard and lossless video output,
- Up to 1500 TVL resolution
- CMOS progressive scan, perfectly capturing the moving object
- DWDR
- Support OSD menu
- High speed, long distance and real time transmission
- LED can be turned on or off automatically
- 24/7 full color image
- 10 ~ 20m LED view distance
- IP67 ingress protection
- Support COC
- Support coaxial audio transmission (Only valid in TVI signal mode)




OSD



Built in Mic



DNR



BLC



Day/Night



WDR



AWB



AGC



IP67

## SPECIFICATION

### CAMERA

|                    |                     |
|--------------------|---------------------|
| Image Sensor       | 1 / 2.5 "CMOS       |
| Resolution         | 5MP                 |
| Image Size         | 2560 x 1936         |
| Video Output       | AHD / TVI /CVI      |
| Audio              | 1CH built-in MIC    |
| Image System       | PAL / NTSC          |
| Electronic Shutter | Auto                |
| LED Distance       | 10 ~20 m            |
| Frame Rate         | 5MP@20fps/4MP@30fps |
| Min. Illumination  | 0 lux ( LED ON)     |
| Lens               | 3.6 mm              |
| Lens Mount         | M12                 |
| S / N Ratio        | ≥52dB ( AGC OFF )   |
| Ingress Protection | IP 67               |

### FUNCTIONS

|                          |                                               |
|--------------------------|-----------------------------------------------|
| Function Control         | OSD ( COC Control )                           |
| Smart LED                | Manual or Auto mode                           |
| Digital WDR              | Yes                                           |
| Digital DNR              | Yes, 2D DNR                                   |
| Global Exposure          | Yes                                           |
| Central Exposure         | No                                            |
| AGC                      | Yes                                           |
| Auto White Balance       | Yes                                           |
| BLC                      | Yes                                           |
| Front Light Compensation | NO                                            |
| Sharpness                | Yes                                           |
| Contrast                 | Yes                                           |
| Image Setting            | Yes                                           |
| Defect Correction        | Auto                                          |
| Language                 | English                                       |
| Angle Adjustment         | Pan: 0°~360°; Tilt: 0°~75°; Rotation: 0°~360° |

### OTHERS

|                     |                                                  |
|---------------------|--------------------------------------------------|
| Power Supply        | DC12V ( ± 15% )                                  |
| Power Consumption   | LED OFF : < 1W; LED ON : < 3W                    |
| Working Environment | - 10 °C ~ 40 °C, 10 % ~ 90 % (relative humidity) |
| Dimensions ( mm )   | Φ 94.6 x 82.8                                    |
| Weight ( net )      | Approx. 0.39KG                                   |