







8MP Stitched 180° Panoramic Network Camera

SIP-VB841-PANA

FEATURES

- Four 2MP video modules to stitch one 8MP (4096x1800), 180°panoramic view stream
- True starlight technology (0.008lux@F2.0 AGC on) provides vivid colour at most scenarios
- 20m Smart IR provides clear and uniform B/W image under no light conditions
- DWDR, 3D DNR, BLC, HLC
- Recognizes max. 50 faces within a public area
- Alarm triggered by multi-rules: line crossing, intrusion, device error
- 5 zones of e-PTZ, 4 zones of privacy masks, and custom logo support
- ONVIF specifications, interoperability between network video products, regardless of manufacturer
- One IP, one cable, reducing total fees



SPECIFICATION

CAMERA MODULE

Image Sensor	1/2.8" progressive scan CMOS image sensor x 4
Image setting	Flip, Mirror, Saturation, Brightness, Contrast, Sharpness, AGC, and AWB adjusted by client software/browser
Shutter Speed	1/1 s – 1/10,000 s
White Balance	Auto/Manual/Indoor/Outdoor
Min. Illumination	Color : 0.008Lux @ (F2.0, AGC ON) ; B/W : 0.008Lux @ (F2.0, AGC ON); c0Lux with IR
Gain	Auto/Manual
Day & Night	IR Cut filter
Digital Zoom	16x
Privacy Mask	4 Programmable privacy masks
3D DNR	Auto /Manual
HLC / BLC	Yes
Defog	Electronic
WDR	D-WDR
EIS	Yes
Regional Exposure	No

LENS

Focus length	3.2mm lens x 4
Aperture	F2.0
FOV	Panoramic image: Horizontal FOV:180° ; Vertical FOV: 85°
Working distance	1.0m ~ INF

IR

IR Range	20m radius
Smart IR	Yes

NETWORK

Max Resolution	4096x1800@25/30fps
Main stream	4096 x 1800, 3840 x 1680 , 2880 x 1264(1~30fps)
Sub stream:	2048 x 896, 704 x 320(1~30fps)
Third stream:	704 x 320 (1~30fps)
SVC	Yes
Video compression	Smart H.265/H.264/MJPEG
Audio compression	G.711 A/U
Audio Enhancement	Not support
Protocols	HTTP, HTTPS, IPv4/IPv6, 802.1x, QoS, FTP, SMTP, UPnP, SNMP,DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP,DHCP, PPPoE
Simultaneous live view	Up to 6 channels
User / Host	Up to 16 users, 3 levels: Administrator, Advanced User and Normal User
Security Measures	User authentication (ID and PW), Host authentication (MAC address); HTTPS encryption, IEEE802.1x port-based network access control; IP address filtering

SMART FEATURES	
Basic event	Motion detection (panorama and original modes support), video tampering alarm, exception (network disconnected, IP address conflict, SD full, SD error)
Face recognition	Max 50 human faces per second(default off)
Face comparison	Default off
Smart Detection	Intrusion detection, line crossing detection, region entrance detection, region exiting detection, target counting
Alarm Linkage	Upload to FTP/Memory card, notify surveillance centre, send email, trigger alarm output, trigger recording, trigger capture
SYSTEM INTEGRATIONS	
Alarm Interface	1CH alarm input; 1CH alarm output
Audio Interface	1CH audio input, 2 to 2.4v[p-p] 1kΩ±10%; 1CH audio output (line out), impedance: 600Ω
Network Interface	1 RJ45 10M/100M Adaptive Ethernet (Support PoE 802.3.af)
CVBS	Not support
RS 485	Pelco-D / P protocol, custom protocols available
Storage	Built-in memory card slot, support micro SD/SDHC/SDXC, up to 256G
USB3.0 /Fiber Optical/GIS	Not Support
API	ONVIF, support SDK and third-party management platform
Client	VMS-9000 and the third-party client
Web Browser	IE8-11 (NOT support Safari /Firefox /Chrome)
GENERAL	
Power	DC12V,PoE (802.3.af), (Max 12.9W, include IR on)
Working Condition	30°C ~ 60°C (-22°F ~ 140 °F), 90%RH less (non-condensing), cold start at -20°C
Storage Condition	-40°C ~ 70°C ;≤ 95%RH
Protection	IP 67, IK 10, 6000V Lightning Protection, Surge Protection and Voltage Transient Protection
Material	Aluminium Alloy; PC
Angle Adjustment	Pan:0~360°; Tilt: 0~90°; Rotation: 0~360°
Dimensions	LxWxH= 288.4mm x 159.7mm x 137.7mm (11.35" x 6.29"x 5.42")
Weight	Approx. 2.1Kg(4.63lb)
Certification	CE, FCC, IK10, IP67
Environment Protection	Complies with Directive EU RoHS, WEEE, Directive 94/62/EC and REACH